

Mini-spectrometers

[S5000-UV]



S5000-UV is a miniature spectrometer configured with crossed Czerny-Turner optical bench. Free Software and Software Development Kit(SDK) is available for spectrum analysis in various applications.

» Features

- Wavelength Range: 190nm ~ 400nm
- Free Software(SpectraPro V3.2 + Spectra V2.0)
- Software Development Kit(SDK) for Windows / Embedded system / Linux
- RS232 Communication Protocol Support for Embedded System
- High Spectral Resolution (FWHM) from 0.2 nm
- High Sensitivity

» Applications

- Gas Concentration Measurements

» Structure

Parameter	Specification	Unit
Dimension	115 mm(L) x 80 mm (W) x 40 mm (H)	mm
Weight	500	g
Connector for Optical Fiber	SMA905	-
Slit	10 5/10/20/25/30/50/100/150/200um Available	um
Grating	1200@210nm	groove/mm
Detector(Image Sensor)	CMOS Linear Image Sensor (UV Enhanced)	-
Number of Pixels	2048	pixels
A/D conversion	16bit high precision AD	-
USB Interface	USB2.0 / USB1.1	
Communication Interface	USB RS232 and LAN is optional	-
Software	Spectra + SpectraPro	-
Software Development Kit(SDK)	Available on Windows / Embedded System / Linux	-

» Absolute maximum ratings

Parameter	Min.	Recommended	Max.	Unit
Power supply (USB Bus Power)	4.5V	5V	+6.0V	V
External Power Supply(Optional)	4.5V	5V	+6.0V	V
Operating temperature	-10°C	25°C	60°C	°C
Storage Temperature	-20°C	25°C	70°C	°C

» **Electrical and Optical characteristics(Ta=25°C, unless otherwise noted)**

Parameter	Min.	Typ.	Max.	Unit
Power Consumption	-	150mA@5V	170mA@5V	mA
Spectral Response Range	-	190nm ~ 400nm	-	nm
Wavelength Accuracy	±0.2	±0.4nm	±0.8	nm
Wavelength Reproducibility	±0.10	±0.12nm	±0.15	nm
Wavelength Resolution	0.10	0.12nm	0.15	nm
Spectral Resolution (FWHM)	0.20	0.25nm	0.45	nm
Wavelength Temperature Dependence	-	0.05	-	nm/°C
Spectral Stray light	0.05	0.2%	0.4	%
Linearity correction	99.0	99.8%	-	-
Numeric Aperture	-	0.22	-	-
Signal to Noise Ratio(SNR)	-	1200:1	-	-
Integration time	-	0.1ms to 10000ms	-	ms

» **Dimensional outline(unit:mm,tolerance unless otherwise noted:±0.5)**

